



DEPLOYED LOGIX
SHELTERS
 THE FIRST IN THE FIELD

X-SERIES SIDE CONNECT

- **NEW MODEL X-SERIES FOR INFINITE FLEXIBILITY.**

- **CONNECTS TO ANY MODEL OF ASAP® OR X-SERIES.**

- **MAXIMIZES FOOTPRINT OF YOUR SHELTER COMPLEX.**

- **MULTI-USE: ENTRY POINT OR CONNECTION CORRIDOR.**

At Deployed Logix we're redefining rapid deployment. Through our extensive work with law enforcement, search and rescue teams, various first responders, private organizations both domestically and abroad, and the military, our team understands that when a crisis calls, seconds count. Discover why we are the leader in American-made, rapidly deployable disaster preparedness products.



Specification and design may be altered without notice due to continuous product development. LAST UPDATED AUGUST 2022.

Proudly made in the USA.
 CAGE CODE: 7CFK2 | DUNS#: 079751064

X-SERIES SIDE CONNECT SPECIFICATIONS

MODEL:	X-24SC	X-40SC
DIMENSIONS (L X W X H):	24.27 x 23.60 x 10 ft (7.40 x 7.19 x 3.05 m)	40.31 x 23.60 x 10 ft (12.29 x 7.19 x 3.05 m)
USABLE SHELTER AREA:	545.37 ft ² (50.67 m ²)	894.24 ft ² (83.08 m ²)
FOOTPRINT AREA:	572.77 ft ² (53.21 m ²)	951.32 ft ² (88.38 m ²)
FOOTPRINT AREA W/ STAKING:	1,151.47 ft ² (106.98 m ²)	1,690.42 ft ² (157.04 m ²)
DOORS:	4	4
WINDOWS (SIDEWALLS // ENDWALLS):	4 // 4	8 // 4
ECU DUCTS:	4 sets	4 sets
STOVE PIPE VENTS:	optional	optional
PERSONNEL REQUIRED:	3 minimum // 4 preferred	6 minimum // 8 preferred
SET UP TIME:	<15 minutes	<25 minutes
SNOW AND RAIN LOAD:	Snow: 10 lb/ft ² (48.8 kg/m ²) Rain: 2 in/hr (50.8 mm/hr)	
WIND RATING:	65 mph, gusts 75 mph (104 kmh, gusts 120 kmh)	
SHELTER WEIGHT:	840 lb (381 kg)	1149 lb (521 kg)
TOTAL SYSTEM WEIGHT:	1170 lb (531 kg)	1649 lb (748 kg)
FRAME SECTION:	4 total	6 total
ROOF:	1 total	1 total
ENDWALL:	2 total	2 total
SIDEWALL:	2 total	2 total

