



3-FOOT MUSCLE WALL

SPECIFICATIONS

- **Material**

- Low density polyethylene
- Elongation to yield: 20%
- Impact strength: 190 ft-lb
- Tensile strength at yield: 2600 psi

- **Dimensions**

- Minimum polyethylene thickness: 0.25"
- Footprint on ground: 11.5 ft²
- 6 ft. wide x 2 ft. deep x 3 ft. high
- Installed in 6 ft. sections
- Fit 192 units on one 48 ft. flatbed trailer

- **Portable**





- Weight per unit (empty): 75lbs
- Weight per unit (filled): 766lbs
- Units nest together for transportation
- 12 walls per bundle

- **All Season Compatible**

- Temperature range: -40° F to 180° F
- 10 year UV rated

- **Ground Pressure**

- Empty: 0.0333 psi
- Filled: 0.3939 psi



FEATURES

• Quick Setup & Take Down

- Male to female connection that slides easily into place with another Muscle Wall
- 3-Foot spring liner clip secures the liner to the Muscle Wall as well as reduces liner tenting
- Reversible, modular corner unit enables the Muscle Wall system to make turns as needed
- Specially designed hand truck can safely move 4 walls at a time

• Intuitive Design

- Two walls nestle together to reduce storage & shipping space
- Threaded top hole cap
- Releasable bung-plug cap for rapid emptying
- Safety ratchet straps restrain adjacent panels
- No pallet required for transportation when using the included forklift hole protectors